



# SETUP SHEET



Easily download setups using our app, which you can find on Google Play and App Store searching for „HMX“. The iOS app requires ORI65193 BLE dongle.

## General Information

Driver:	Date:
Track:	Surface:
Temp.:	

ESC Firmware:
Motor:
Endbell Timing:
Rotor:
Final Ratio:

Max. ESC Temp.:	Min. Battery Voltage:
Max. Motor Temp.:	Max. Motor RPM:

## Basic Settings

Drive Mode:	Fwd/Brk	Fwd/Rev/Brk	Fwd/Rev
Drag Brake:		Neutral Range:	
Cut-Off Voltage:	V	Top Speed:	
Punch:		Blinky Mode:	On Off
Max. Torque:		BEC Voltage:	6V 7.4V
Max. Brake:	%	Number of Cells:	
Initial Brake:	%	Overheat Protection:	On Off*
Brake Frequency:		Number of Poles:	

\*No warranty if overheat protection is turned off.

## Timing Settings

Timing 1 Start:	RPM
Timing 1 Scale:	RPM/DEG
Timing 2 Start:	RPM
Timing 2 Scale:	RPM/DEG
Max. Timing:	DEG
Turbo Delay:	SEC
Turbo Slope:	DEG/0.1 SEC

Warning: change timing settings carefully (only small changes at a time). Wrong settings may damage your ESC and/or motor.

## Comments